

MINI Pool Heat Pump



Features

- Streamline & Cute design.
- Easy handy lift.
- Safe inner screw water connection
- Pluf & play dual protection with RCD
- Robust structure ideal for express
- Plastic & Metal innovative mixed colors
- Low noise with integrated fan
- Stand feet for easy drainage

Model No.	Mini-HP 3	Mini-HP 4	Mini-HP 5.2
Heating Capacity at Air 26°C, Humidity 80%, Water 26°C in, 28°C out			
Heating Capacity (kW)	3.00	4.00	5.00
Power Input (kW)	0.58	0.77	0.97
COP	5.17	5.20	5.17
Heating Capacity at Air 15°C, Humidity 70%, Water 26°C in, 28°C out			
Heating Capacity (kW)	2.30	2.90	3.85
Power Input (kW)	0.55	0.69	0.92
COP	4.18	4.20	4.18
Power supply	220-240V / 1 / 50 Hz		
Max Power Input (kW)	0.7	0.9	1.1
Max Current (A)	3.2	4.8	5.8
Water Flow Volume (m ³ /h)	1.5	2.0	2.5
Advised pool size m ³	0~10	5~16	8~20
Refrigerant	R32		
Water connection (mm)	32 or 38		
Heat Exchange	Titanium		
Air Flow Direction	Horizontal		
Working temp. range (°C)	12~43		
Casing Material	ABS+Metal		
Noise level dB(A) 10m	45	46	48
Net Weight (kg)	18	22	26
Gross Weight (kg)	20	24	30
Net Dimensions (mm)	380*290*370		420*365*440
Package Dimensions (mm)	440*355*400		480*435*490